

PRELIMINARY



SLM 1476CM
(Front-panel is depicted in this prototype image)

Applications

CATV installation and troubleshooting

Off-air 8-VSB reception-broadcast footprint quality

Private cable systems in schools, corporate campuses, correctional institutions and medical centers, anywhere RF is used

Custom home theater installation and calibration

SLM 1476CM Portable Signal Level Meter

The SLM 1476CM provides everything installers and operators are looking for in a signal level meter. Capable of analog and digital measurements, including Pre/Post BER, MER, Spectral Display, DOCSIS 2.0 Network Testing, and Leakage and Ingress Testing capabilities - all at an affordable price. Designed to easily test multiple DOCSIS channels. The SLM 1476CM also provides a pass/fail test which can then be saved and sent back upstream to the CMTS for paperless documentation.

Key Features

- 1-button testing for simple operation
 - Alpha/Numeric keypad for direct channel or frequency entry
 - Use the SLM 1476CM for complete modem installation. Test both forward and return from premise to CMTS
 - Digital measurement capabilities including: Average power, Pre/Post BER, MER, and Constellation for QAM, also provides 8-VSB/ATSC testing capabilities.
 - All Channel/Frequency Tuning: From 4-1000 MHz (UHF/VHF/CABLE) allowing return path signal testing as well as testing high-frequency channels with ease
 - Analog measurement capabilities including Signal Level, A/V ratio, and C/N
 - Signal leakage testing capabilities ensures every installation is clean and meets system requirements
 - Ingress capabilities allows for both forward and return path testing from the ground block or line extender to ground block for unwanted noise
 - Full featured spectral display enables you to view all channels, a single channel, or a bar graph display for a quick visual of inspection of all channels.
 - Data logging enables the technician to save or print all data for future reference or record of completed installations. Connect to PC via USB cable and download using FREE interface software
 - 12-volt AC/DC charging and Auto-off for battery saving operation
 - Threshold test-user definable thresholds for pass/fail logging
 - Log file transfer over DOCSIS connection to CMTS
- * DOCSIS 2.0 and Compatible with DOCSIS 3.0 Networks

SLM 1476CM

Portable Signal Level Meter

Specifications*

Automated or Manual Spectrum Analysis

Frequency Range:	TV and Radio 4-1000 Mhz
Frequency Resolution:	62.5 Khz
RF Input Impedance:	75 ohms
DOCSIS Input Impedance:	75 ohms
Dynamic Range:	15 dBuV to 125 dBuV or -45 to +65 dBmV or -98 to +16 dBm
Measurement Resolution:	0.1 dB
Level Measurement Acc:	1 dB typ. (2 dB max.)
A/V Ratio:	1.5 dB typ. (2 dB max.)
C/N Ratio:	2 dB typ. (4 dB max.)
Measure Filter Bandwidth:	100 Khz @ -3 dB
Custom Channel Plans:	25

Digital Measurements- 8-VSB, QAM 16-32-64-256 (Annex A/B)

Frequency Band:	4-1000 Mhz
Power Measurement	
Dynamic Range:	From -35 to 56 dBmV
BER Measurement:	bBER up to 1×10^{-8}
(after Reed Solomon)	aBER up to 2×10^{-9}
MER Measurement:	17 dB to 36 dB
Constellation Display:	64-128-256 (on graphics display)

DOCSIS Measurements

DOCSIS 2.0 Compliant Device	
Frequency Band:	5-1000 Mhz
Input Impedance:	75 ohms
Range:	-45 to +65 dBmV
Measurements Include:	Level, MER, Pre/Post BER, Lost Packet, Transmit Power, Transmitted Packets, Received Packets, PER, Latency Min/Max/Avg
MAC Address:	Default or User Defined Measurements for Downstream, Upstream, and IP Status

General Specifications

Power Supply:	Built-in NiCd rechargeable battery External Power Supply 17 VAC or 20 VDC 1A
Battery Duration at 25°C:	4-6 Hours in Analog 3-4 Hours in Digital
Size:	H 11.8" x W 4.33" x D 2.36"
Download Port:	USB
Display:	128 x 128 pixels, 2.5" square
Front-panel:	Numeric Keypad

* All Specifications and features are preliminary, and subject to change.

Since 1951, Sencore has provided our customers with innovative operational, signal monitoring and analysis, and video/audio distribution equipment. Sencore continuously works in close collaboration with our customers to provide solutions for the communications delivery challenges of today and tomorrow. All Sencore products are backed by unsurpassed customer support and responsiveness