



**EASY OPERATION • EXTERNALLY REPLACEABLE INPUT CONNECTOR • RECHARGEABLE BATTERY WITH CHARGER
• LOW BATTERY INDICATOR LED • LIGHTWEIGHT, COMPACT SIZE • INCLUDES CARRYING CASE • TWO-YEAR WARRANTY**

The Spectrum II Signal Level Meter from Trilithic offers quick drop level testing. It's easy to operate and delivers a superior accuracy rating of ± 1 dB.

Simply connect the meter to a local drop, depress the LO or HI button and the LED dot bar will automatically display the channel level reading. The user instantly knows if a drop is functioning properly by comparing the levels to system specifications.

The Spectrum II comes standard with a holster-style padded carrying bag, rechargeable NiCad battery, battery charger, and a replaceable input connector. You also get Trilithic's TWO-YEAR WARRANTY—the best in the industry.

SPECTRUM II SPECIFICATIONS

FREQUENCY RANGE: LO channel - 60.00 MHz, 61.25 MHz, 3
66.00 MHz or 67.25 MHz 4
HI channel - 204.00 MHz, 205.25 MHz, 12
210.00 MHz, 211.25 MHz, 13
294.00 MHz, 295.25 MHz, 36
300.00 MHz, 301.25 MHz, 37
390.00 MHz, 391.25 MHz, 52
396.00 MHz or 397.25 MHz 53

LEVEL MEASUREMENT RANGE: -5 to +15 dBmV

MEASUREMENT ACCURACY: ±1 dB @ 77°F (25°C); ±2 dB over operating temperature

IMPEDANCE: 75 Ohms

OPERATING TEMPERATURE: 32° to 120°F (0° to 50°C)

POWER: Internal rechargeable NiCad battery with external charger. 110 VAC/60 Hz or 220 VAC/50 Hz.

WEIGHT: 10 oz. (0.28 kg)

DIMENSIONS: (HxWxD) 5.75" x 3.5" x 1.0" (146mm x 89mm x 25mm)

For more information,

Contact your local representative at:

0391F10000

Or, contact us at:

 **TRILITHIC**

9202 E. 33rd Street
Indianapolis, IN 46236 USA
(800) 344-2412 / (317) 895-3600
FAX: (317) 895-3613